



**CRITICARE**  
TECHNOLOGIES, INC.

## VitalCare™ 506NV3 TurboTemp™ Monitors

*Proprietary ComfortCuff™ NIBP, pulse oximetry, and predictive temperature in one compact, easily transported monitor. Ideal for spot-checks or continuous vital signs monitoring.*

### 506NV3 TurboTemp Models

**DNVP3:** DOX™ SpO<sub>2</sub>, NIBP, temperature and printer

**LNVP3:** OxiMax™ SpO<sub>2</sub>, NIBP, temperature and printer

### Features

- Proprietary *ComfortCuff™* NIBP measures on inflation for faster, more comfortable readings.
- Alaris TurboTemp™ predictive temperature for fast, accurate measurements.
- Choice of Criticare DOX™ digital SpO<sub>2</sub> technology or Nellcor OxiMax™ SpO<sub>2</sub> technology.
- Audible and visual alarms are adjustable providing instant notification the way you need them.
- Optional internal printer for on-demand, automatic interval, trends or multi-patient reports.



**Spot-check or continuously monitor three critical parameters on neonates to adults with a single monitor.**

Designed to travel everywhere you do, the VitalCare 506NV3 TurTemp patient monitors with integrated carry-handle attach quickly and easily to IV pole mount or rolling stand. Available in multiple configurations – with choice of Criticare or Nellcor oximetry – the 506NV3 patient monitors provide maximum versatility and cost-effectiveness.

New smart battery management allows up to 100 NIBP measurements on a single charging. With a compact design that is easily setup for spot-check readily to hospital, clinic and transport requirements.

# VitalCare™ 506NV3 TurboTemp™ Monitor

## Technical Specifications

### Non-Invasive Blood Pressure

Technique:	Oscillometric measure upon inflation
Measurement Time:	<40 seconds typical
Automatic Measurement Cycles:	1 - 60 minute; 2 - 4 hour; STAT
Inflation Pressure Range:	30 to 300mmHg (Adult) 30 to 150mmHg (Pediatric) 20 to 150mmHg (Neonate)
Resolution:	1mmHg
Clinical Accuracy:	SP-10:2002
Transducer Accuracy:	±2mmHg or ±2% of reading, whichever is greater, over full range
STAT mode:	5 minutes of consecutive readings

### Pulse Oximetry

Range:	1% to 99%
Resolution:	1%
Accuracy (DOX only):	70% to 99% range: ±2%; 50% to 69% range: ±3%; <50%: unspecified
Accuracy (OxiMax Only):	70% to 99% range: ±2%; <70%: unspecified
Method:	Dual wavelength LED
Audio:	Tone with each detected pulse; pitch varies with saturation

### Heart (Pulse) Rate

Range:	20 to 300bpm
Accuracy (DOX only):	Greater of ±1bpm or ±1%, of reading Unspecified for <30 or >240 bpm
Accuracy (OxiMax only):	Greater of ±1bpm or ±1%, of reading Unspecified for <30 or >240 bpm
Update Time:	Every second
Resolution:	1bpm
Pulse Volume:	10 levels or Off

### Temperature

Type:	Alaris TurboTemp™
Method:	Predictive or Continuous
Channels:	1
Predictive Mode Range:	96.0° to 106° F (35.6° to 41.1° C)
Continuous Mode Range:	80.0° to 106° F (26.7° to 41.1° C)
Accuracy:	±0.2°F (±0.1°C) (measured in calibrated water bath in continuous mode)
Resolution:	0.1° F or 0.1° C
Response Time:	10 seconds typical (oral measurements)
Probes:	CAT 1544 Oral, CAT 1545 Rectal
Probe Covers:	CAT 447 (P850A)

### Alarms

Indication:	Audible; Visual
Volume:	10 levels or Off
Silence:	Yes; 2 minutes or permanent

### Trend Memory

Memory:	Last 24 hours
Parameters:	SpO <sub>2</sub> , pulse rate, NIBP, temperature
Report Types:	Single Patient or Multi-patient; Selectable formats

### Displays

Type:	LED
Parameters:	NIBP, SpO <sub>2</sub> ; temperature, pulse rate; pulse bar
Status:	Alarm Silence; Sensor; Low Battery; External Power; Patient Size
Text:	Alphanumeric LCD
Languages:	English, Spanish

### System Output

Com Port:	Serial, RS 232-compatible
-----------	---------------------------

### Printer

Type:	Thermal array
Tabular Mode:	1 - 60 minute intervals; 2 - 24 hour intervals; Auto on BP; Auto on Alarm, Off

### Mechanical

Weight:	Base unit with battery: 6.95 lb; 3.15kg
Size:	Base unit: 8.7" (H) x 7.1" (W) x 6.5" (D); 22cm (H) x 18cm (W) x 16.5cm (D)

### Power Requirements

Voltage:	100 to 240 VAC, 50 to 60 Hz
Battery:	Sealed lead acid; Life: 8 hours Rechargeable: 6 hours

### Environmental

Operating Temperature:	32° to 113° F; 0° to 45° C
Storage Temperature:	23° to 122° F; -5° to 50° C
Operating Humidity:	15% to 90%, non-condensing

### Classification

Type of Protection:	Class I equipment
Degree of Protection:	Type CF defibrillator-proof equipment
Protection against Ingress:	IPX1 rating, Drip-Proof Equipment



Specifications subject to change without notice.